

## CLAIMS

I claim:

Sub  
B1

5

1. A system to remotely configure a radio, comprising:

a graphical interface on a first network device that displays an association page that establishes an association list between a first set of configuration data with a second set of configuration data in a user profile in a remote database; and

a radio having a digital controller that is able to communicate with the remote database to retrieve and apply the user profile to facilitate operation of the radio.

10

Sub  
B2

2. The system of claim 1, wherein a plurality of preset button identifiers is

the first set of configuration data; and

a plurality of radio stations is the second set of configuration data.

15

Sub  
B1

3. The system of claim 2, further comprising:

a preset button in a plurality of buttons located at the radio being associated with a radio station in response to receipt of the association list at the radio.

20

4. The system of claim 1, further comprising:

a location identifier identifies radio stations that are included in the first set of configuration data.

Sub  
B1

5. The system of claim 1, further comprising:

an alarm configuration page displayed in the graphical interface that establishes an alarm time list with an associated alarm type in the user profile.

5  
Sub  
B1 A2

7. The system of claim 6, wherein an alarm clock in the radio is set in

response to receipt of the alarm list and the associated alarm type from the user profile.

8. The system of claim 6, wherein receipt of a time synchronization message

at the radio results in the alarm clock being set.

Sub  
B1

9. The system of claim 1, wherein the graphical interface is a web browser.

10. A method for remotely configuring a radio, comprising:

displaying on a graphical interface on a first network an association page that establishes an association list between a first set of configuration data with a second set of configuration data in a user profile in remote database; and

retrieving the user profile by a digital controller in the radio that is able to communicate with the remote database to facilitate the operation of the radio .

11. The method of claim 10, further comprising:

entering a location identifier at the graphical interface;  
sending the location identifier to the remote database;  
identifying the second set of configuration; and

receiving at least the second set of configuration data the first computing device.

12. The method of claim 10, further comprising:

generating a time synchronization message at the second computing device;

5 sending the time synchronization message to the radio; and

setting a clock in the radio in response to reception of the time synchronization message.

13. The method of claim 10, further comprising:

displaying an alarm configuration page in the graphical user interface;

creating an alarm association between an alarm action and a time of day;

storing the alarm association in the user profile located in the remote database;

and;

communicating the alarm association to the radio.

14. The method of claim 10, wherein establishing further includes:

assigning a first preset button identifier from a plurality of preset button that  
comprise the first set of configuration data to a radio station from a plurality of radio  
stations that comprise the second set of configuration data.

15. The method of claim 14, wherein communicating further includes:

configuring a first preset button in a plurality of preset buttons in the radio to  
select the radio station upon the selection of the first preset radio button.

16. A data structure in a user profile located in a database, comprising:  
a user profile identifier;  
a plurality of preset button identifiers linked to the user profile identifier; and  
an association between each of the plurality of preset button identifiers and one of  
a plurality of radio stations.

17. The data structure of claim 16, further comprising:  
a plurality of alarm times linked to the user profile identifier; and  
an alarm type linked to each of the plurality of alarm times.

18. The data structure of claim 17, wherein the alarm type is either a radio  
station or a buzz.

19. A system for remotely configuring a radio, comprising:  
means for displaying on a graphical interface on a first network an association  
page that establishes an association list between a first set of configuration data with a  
second set of configuration data in a user profile in remote database; and  
means for retrieving the user profile by a digital controller in the radio that is able  
to communicate with the remote database to facilitate the operation of the radio .

20. The system of claim 19, further comprising:

means for entering a location identifier at the graphical interface;  
means for sending the location identifier to the remote database;  
means for identifying the second set of configuration; and  
means for receiving at least the second set of configuration data the first  
5 computing device.

21. The system of claim 19, further comprising:

means for generating a time synchronization message at the second computing  
device;  
10 means for sending the time synchronization message to the radio; and  
means for setting a clock in the radio in response to reception of the time  
synchronization message.

22. The system of claim 19, further comprising:

15 means for displaying an alarm configuration page in the graphical user interface;  
means for creating an alarm association between an alarm action and a time of  
day;  
means for storing the alarm association in the user profile located in the remote  
database; and  
20 means for communicating the alarm association to the radio.

23. The system of claim 19, wherein the step establishing further includes:  
means for assigning a first preset button identifier form a plurality of preset button  
that comprise the first set of configuration data to a radio station from a plurality of radio  
stations that comprise the second set of configuration data.

5

24. The system of claim 23, wherein the means for communicating further  
includes:

means for configuring a first preset button in a plurality of preset buttons in the  
radio to select the radio station upon the selection of the first preset radio button.

Add  
B1

10